


Alfatronix 12V/24V USB Chargers



Rear Mounting



Rear Mounting



Front Mounting

When we looked for a suitable USB Charger to add to our range it was an easy decision to add the alfatronix range, fitted as standard equipment on High End MotorHomes, Trains and Coaches. These Chargers built in Poole UK offer exceptional performance and build quality. These units are capable of charging all current tablet and phones unlike cheaper units on the market.



Pod Mounting

Part Number	Description (mm)	Dimensions (mm)
PVPRO-S	Single Output 12/24-5V USB Charger 2.1A	37 X 33: Hole Ø30
PVPRO-D	Double Output 12/24-5V USB Charger 3.0A 2x1.5A	37 X 33: Hole Ø30
PVPRO-Sff	Single Output 12/24-5V USB Charger 2.1A	47 X 33: Hole Ø30
PVPRO-Dff	Double Output 12/24-5V USB Charger 3.0A	47 X 33: Hole Ø30
PV-USB-Pod	Mounting Pod for USB Chargers	60 x 52 x 80
PV-USB-H1	Standard 1.2m wiring with inline fuse 2A fuse	

Technical Data:

Input voltage: 9-32Vdc

Output Power: 5Vdc +/- 0.2V

Application: Charges all USB devices including Apple and Android

Operating Temp: -25c to +55c

Operating Humidity: 95% max, non condensing

Casework: Black Polycarbonate Body

Connections: Input 6.3mm push in flat blade

Output USB Type A Single/Double Socket - tested to 10000 times

Output Indicator: Blue LED Output Indication

Mounting Method: 30MM Diameter Hole

Approvals: 2014/30/EU The general EMC directive, Regulation 10 The automotive directive

93/68/EEC The CE marking directive, AES5, ECE R118.02 and UL 94: V-0

Markings: CE and E

EN50498, EN61373 and ISO 7637-2